



电性参数

Ta=25 Absolute Maximum Rating(ta=25)

Parameter	Symbol	Value	Unit
Max Power Dissipation	PD	50	mW
Max Continuous Forward Current	IF	20	mA
Peak Forward Current	IFP	80	mA
Max Reverse Voltage	VR	5	V
Antistatic ability	ESD	2000	V
Operating Temperature Range	TOPR		
Storage Temperature Range	TSTR		
/ Lead Soldering Temperature/Time	TSOL	260 ≤ 6S	/

≤ ≤ ≤ ≤

光电参数 Ta=25 Optical-electrical parameter(ta=25)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test conditions
Luminous Intensity	Iv	80	/	180	mcd	IF=20mA
Dominant Wave Length	λ d	600	/	606	nm	IF=20mA
Peak Wave Length	λ p	/	605	/	nm	IF=20mA
Forward Voltage	VF	1.9	/	2.4	V	IF=20mA
Viewing Angle	2θ1/2	/	120 °	/	deg	IF=20mA
(Half wave width)		/	20	/	nm	IF=20mA
Reverse Current	IR	/	/	≤ 1	μ A	VR=5V











使用注意事项（2）

Precautions (2)

3. 设计建议

Design Consideration

LED

