XL-PD438B **技术数据表 Technical Data Sheet**

特点（characteristic）：

* L/W/H :6.6*4.8*3.8 mm

Outline Dimensions (L / w / h): 6.6x 4.8 x 3.8mm

* : /

Luminous color and colloid: infrared receiver tube black colloid

* ROHS

Environmental protection products Complied With ROHS Directive

* MSL :3

Moisture sensitivity level MSL : 3 levels

* EIA

EIA standard packaging

*

High energy efficiency, fast startup

应用领域（product application）：

*

Medical equipment

*

Infrared remote controller

*

Camera monitoring head

*

Industrial control: counters, thermal imaging, smart meter

*

Infrared photoelectric switch

*

Wireless communication and signal transmission

* ,

Intelligent car, robot



目录
Catalogue

Electrical Characteristics.....3

Typical Characteristic Curves.....5

Outline Dimensions.....6

Packaging.....7

Precautions.....9

电性参数

Electrical Characteristics

Parameter	Symbol	Maximum rating	Unit
Power consumption	Pd	150	mW
Reverse Voltage	VR	32	V
Operating ambient temperature	Topr	-40°C ~ +85°C	
Storage ambient temperature	Tstg	-40°C ~ +85°C	
Welding conditions	Tsol	260 ≤ 6S	

Initial Electrical Optical Characteristics Ta=25

Parameter	Symbol	Min	Representative	Max	Unit	Condition
Open-Circuit Voltage	VOC	/	0.35	/	V	=940nm Ee mW/cm2
Short-Circuit Current	Isc	/	18	/	μA	=940nm Ee mW/cm2
Reverse Light Currente	IL	15	25	/	μA	=940nm V_R=5V Ee mW/cm2
Reverse Dark Current	ID	/	5	30		

40V

典型特性曲线

Typical Characteristics Curves





外形尺寸

Outline Dimension



(Note)

1.

Dimensions are in millimeters

2. ± 0.30mm

Tolerances unless mentioned are ± 0.30mm

包装

Packaging

Moisture Proof and Antti-Electrostic Foil Bag



Label Expantion



使用注意事项（2）

使用注意事项（3）