

XL-DZT502UYD1 F5

Technical Data Sheet


特点 (characteristic) :

- * :F5/11.3*15.0*10.3mm
- Appearance dimension: F5/11.3*15.0*10.3mm
- * : /
- Luminous color and colloid:yellow brightness White /yellow colloid
- * ROHS
- Environmental protection products meet ROHS requirements
- * MSL :2
- Moisture sensitivity level MSL : 2 levels
- * EIA
- EIA standard packaging
- *
- Long operating life
- * 4
- High energy efficiency, fast startup
- *
- Low voltage DC drive



应用领域 (product application) :

- * 4 4 ;
- Home appliances, digital, communication
- *
- Automotive Electronics
- *
- Lighting decoration
- *
- electronic toy
- *
- electronic clock
- *
- Traffic instructions
- *
- Medical beauty instruments
- *
- Electronic teaching equipment
- *
- Urban lighting



目录

Catalogue

Electrical Characteristics.....3

Typical Characteristic Curves.....5

Outline Dimensions.....7

Packaging..... 8

Precautions..... 9

电性参数

Electrical Characteristics

Absolute Maximum Ratings Ta=25

Parameter	Symbol	Rating	Unit
Consumed power	Pd	50	mW
Max Continuous Forward Current	IF	20	mA
Peak Forward Current	IFp	80	mA
Operating ambient temperature	Topr	-40℃ ~ +85℃	
Storage ambient temperature	Tstg	-40℃ ~ +85℃	
Welding conditions	Tsol	reflow soldering 240℃ 6s manual welding 300℃ 3s 2.0mm	

Initial Electrical Optical Characteristics Ta=25

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test conditions
Luminous Intensity	Iv	300	/	1500	mcd	IF=20mA
Dominant Wave Length	λd	585	/	595	nm	IF=20mA
Peak Wave Length	λp	/	588	/	nm	IF=20mA
Forward Voltage	VF	1.8	2.2	2.4	V	IF=20mA
Viewing Angle	2θ1/2	/	35	/	deg	IF=20mA
Spectral Width at half height	Mλ	/	20	/	nm	IF=20mA
Reverse Current	IR	/	/	0.5	μA	VR=5V

亮度分档:

Brightness grading:

电压分档:

Vol

可靠性试验

Reliability Test Items And Conditions

外形尺寸

Outline Dimension

~~26.00~~

0

(Note)

1.

包装

Packaging

*



使用注意事項 (2)

Precautions (2)

5. Weld

2mm

LED

LED 

When welding, welding must be conducted below 2mm of colloid bottom. When welding, try to avoid soaking LED colloid. After welding, avoid adding external force on the pin or shaking LED colloid.

6. Drive way

LED

LED

A

LED



In the current driving mode of LED, if LED is multiple in parallel, it is recommended to use line A and add a flow limit resistance to each LED to ensure the consistent brightness of LED.

Circuit model A

Circuit model B  d

使用注意事项目 (3)

Precautions (3)

8、其他事项:

Others

*

山

山

*When handling the product, touching the encapsulant with bare hands will not only contaminate its surface, but also affect on its optical characteristics. Excessive force to the encapsulant might result in catastrophic failure of the LEDs due to die breakage or wire deformation. For this reason, please do not put excessive stress on LEDs, especially when the LEDs are heated such as during Reflow Soldering.

