XL-DZ304UBD/4 技术数据表

F3MM

特点

* Fe's
* Appearance

# 目录

Catalogue

**亮度分档**

# 典型特性曲线










: 25 + 5 C./Note: If not otherwise indicated, the test environment temperature is 25 + 5 C.

# 可靠性试验

## Reliability Test Items And Conditions

C J

# 外形尺寸




(Note)

1.

Dimensions are in millimeters.

2. Ñ 0.25mm .

Tolerances unless mentioned are Ñ 0.25mm.

使用注意事项（ ）

## 使用注意事项（ ）

**4、其他事项：**

*

*When handling the product, touching the encapsulant with bare hands will not only contaminate its surface, but also affect on its optical characteristics. Excessive force to the encapsulant might result in catastrophic failure of the LEDs due to die breakage or wire deformation. For this reason, please do not put excessive stress on LEDs, especially when the LEDs are heated such as during Reflow Soldering.



*LED

*The epoxy resin of encapsulant is fragile, so please avoid scratch or friction over the epoxy resin surface. While handling the product with tweezers, do not hold by the epoxy resin, be careful.

**5、眼睛保护忠告：**

*LED LED

*Viewing direct to the light emitting center of the LEDs, especially those of great Luminous Intensity, will cause great hazard to human eyes. Please be careful.

If there are any modifications