目录
Catalogue

Electrical Characteristics.....3

Typical Characteristic Curves.....5

Reliability Test Items And Conditions.....6

Outline Dimensions.....7

Packaging.....8

Precautions.....9

电性参数

Electrical Characteristics

Absolute Maximum Ratings Ta=25

Parameter	Symbol	Red	YG	Unit
[redacted]				

亮度分档:

Brightness grading:

代码 Code	最小值 Min	最大值 Max	单位 Unit	测试条件 Test conditions
A2				

[redacted]:

Voltage grading:

波长分档:

Wavelength grading:

典型特性曲线

Typical Characteristics Curves

光谱分布曲线
Relative Spectral Distribution



伏安特性
Volt ampere characteristic

正向电流降额曲线
Forward current derating curve



相对光强与正向电流特性
Relative Luminous VS Forward Current



光强与环境温度曲线



相对辐射强度与空间角度关系

可靠性试验

Reliability Test Items And Conditions

Class	Test item	Testing environment	Testing time	Qty	Fail qty
Endurance test	Working life	Ta=25 ±5 ,IF=20mA	1000hrs	22 PCS	0/1
	High temperature and high humidity experiment	Ta= 85±5 , RH= 85 90%	1000hrs	22 PCS	0/1
	High-temperature storage	Ta= 85±5	1000hrs	22 PCS	0/1

外形尺寸

Outline Dimension

ensεons

(Note)

1.

Dimensions are in millimeters.

2. Ñ 0.50mm .

Toleranv "Ñ

包装

Packaging

*

In Bags

*

Moisture Proof and Anti-Electrostatic Foil Bag



5.

使用注意事项（3）

Precautions (3)

4、其他事项：

Others

*

*When handling the product, touching the encapsulant with bare hands will not only contaminate its surface, but also affect on its optical characteristics.