
XL-IR

目 录

Catalan

电性参数
Electrical Characteristics.....3

典型特性曲线
Typical Characteristic Curves.....7

可靠性实验
Reliability Test Items And Conditions.....8

外形尺寸
Outline Dimensions.....9

包装
Packaging.....10


使用注意事项
Precauti recauti precauti precauti precauti precauti precauti precauti m "r P

自性参数

Electrical Characteristics

Absolute Maximum Ratings		Ta=25	
Parameter	Symbol	Rating	Unit
		2	6

Initial Electrical Optical Characteristics				Ta=25		
Parameter	Symbol	Min.	Typ.	Max.	Unit	Test conditions
	ICC	0.3	0.4	0.5	mA	VDD=5V
center	L 0 °	10	15	-	M	
	L 35 °	5	6	-	M	/
	L 35 °	5	6	-	M	
BPF	f _o	-	37.9	-	KHZ	/
	f _{BW}	-	6	-	KHZ	/
	V _{oI}	-	-	250	mV	Isink=2.0mA
	V _{oh}	4.5	-	5.0	V	VCC=5V
	T _{pwl}	400	600	800	us	burst wave Vin=500UVp-p
	T _{PWH}	400	640	800	us	burst wave Vin=50mVp-p





Parameter	Symbol	Min.	ij
-----------	--------	------	----



接收距离分档:
Receive distance grading


代码 Code	最小值 Min	最大值 Max	单位 Unit	测试条件 Test conditions

工作电压分档:
Working voltage grading

代码 Code	最小值 Min	最大值 Max	单位 Unit	测试条件 Test conditions

工作电流分档:
Working current grading

代码 Code	最小值 Min	最大值 Max	单位 Unit	测试条件 Test conditions



典型特性曲线

Typical Characteristics Curves

Test waveform





Figure 4. Typical Bandpass Curve

Figure 4. Supply Current vs supply voltage





可靠性试验

Reliability Test Items And Conditions

* Reliability Test Project

	260 ± 5	5	20	20
	100PF 1.5KΩ , 4KV ,		20	20





焊接指南 (1)

Guideline for Soldering (1)


使用烙铁手工焊接

Hand Soldering

30

2. 回流焊接:

Reflow Soldering:



焊接指导 (2)


使用注意事項

使用注意事項 (3)

Precautions (3)

3. 其他事項:

Others



HH

M 2K