


Sur gxfw ihdwxuhv

- * 35mW TC = 25°C
- Optical output power (continuous wave): 35mW (TC = 25°C)
- * 520nm
- Typical emission wavelength: 520nm
- * TO-56
- Metal TO-56 package
- *
- Efficient radiation source for cw and pulsed operation
- *
- Single mode semiconductor laser
- *
- High modulation bandwidth
- * MSL :2
- Moisture sensitivity level MSL : 2levels
- * ROHS
- Environmental protection products meet ROHS requirements

Dssolfdwlr qv

- * LiDAR/Tof
- Lidar (LiDAR/Tof) and Range Measurement
- *
- Industrial Detection and Safety Sensing
- *
- Medical and Biophotonics
- *
- Military and National Defense
- *
- Research and Quantum Technology
- *
- Consumer Electronics and Security Systems






Absolute Maximum Ratings Ta=25

parameter

symbol





						w s	p d{
		λ					
		θ					o
		θ					o
		$\Delta \theta$					
		Δ					o




外形尺寸

Rxwolqh Gl phqvlr q



包装

Sdfndjlqj



使用注意事项

Suhfdxwlr qv


41 Ihhw dvvh p e0|

1 2

It must be 2 mm from the colloid to bend the bracket.

2 PCB

Welding must be performed at normal temperatures. Once the laser diode has been properly mounted onto the PCB, avoid applying mechanical pressure to its pins whenever possible.



51 Hohfwur vwdwlf surwhfwlrq

“ ”

HBM

<800V

250V-500V <100V

Plastic-coated laser diodes do not have a fixed "protection voltage" value; their electrostatic sensitivity typically ranges from <800 V on the HBM human model, with actual tolerance usually limited to 250–500 V. Protection measures must be implemented according to the <100 V operating standard.

61

During laser operation, avoid exposure of the eyes and skin to laser radiation.

If there are any modifications to the specification sheet, no further notice will be given.

